

## THICKNESS PLANING MACHINE



**530**

**630**

### TECHNICAL DATA

|                                       |         | <b>530</b> | <b>630</b> |
|---------------------------------------|---------|------------|------------|
| Motor power                           | Kw (Hp) | 4 (5,5)    | 5,5 (7,5)  |
| 4-knives surface shaft Ø              | mm      | 120        | 120        |
| Rotation speed of surfacing shaft     | r.p.m.  | 5000       | 5000       |
| Suction hood Ø                        | mm      | 160        | 160        |
| Overall dimensions of cast iron table | mm      | 930x530    | 930x630    |
| Working height min / max              | mm      | 5 / 300    | 5 / 300    |
| 4-infeeding speeds                    | m/1'    | 7-11-15-19 | 7-11-15-19 |
| Net weight                            | kg      | 650        | 750        |

### STANDARD EQUIPMENT

- Manual delta/star switch
- Overload protection and emergency switch
- Electric rise/fall of the table
- Mechanical height gauge
- Magnetic adjusting knives device
- In-feeding roller in front of the thickness table
- Suctioning hood
- Maintenance manual and spanners

### EQUIPMENT FOR "CE" NORMS

- Electric rise/fall of the table
- Mechanical height gauge
- Magnetic adjusting knives device
- In-feeding roller in front of the thickness table
- Suctioning hood
- Self-braking motor
- Low tension switchboard
- Automatic delta-star switch
- Maintenance manual and spanners

| Mod.   |        | Code  | STANDARD VERSION | Code    | « CE » VERSION |
|--------|--------|-------|------------------|---------|----------------|
| PS 530 | EURO € | ps530 | 11.480,00        | ps530ce | 12.290,00      |
| PS 630 | EURO € | ps630 | 11.995,00        | ps630ce | 12.720,00      |

Price FOB Origin Italy

<https://baibus.africa>